

HATlite



- Rubber housing for extreme rough applications
- Customized assembling of joysticks, push buttons and display
- Graphic display 128 x64 dots with backlight for indicating HATOX-specific data (signal strength, battery condition, frequency indication, etc.) and data feedback via CAN-bus
- Disposable standard AA-batteries or rechargeable batteries may be used
- Permanent operation up to 40 hours possible (without backlight) with rechargeable batteries of 2700 mAh
- "Listen before talk"-technology with automatic frequency management for higher operational safety or frequency hopping for USA and Canada
- Several systems can be operated at the same time without disturbing each other

Technical data is subject to change without notice

General technical data

Temperature range	–20° to +80°C (optionally with heating foil –40° to +80°C)
Type of protection	IP 65 (higher on request)
Housing	TPE
Technology	Transceiver (bidirectional, half-duplex)
Frequency	433.075–434.775 MHz (69 channels) / Europe / 902–928Mz / USA & CANADA
Output Power	adjustable up to 10 mW
Modulation	FSK
Transmission method	TDMA (Time Division Multiple Access) with
technology for Europe; frequency hopping for USA	Distance
approx. 300 meters / 1000 feet (depending on environment)	Supply voltage
2 x AA-NiMH-cells (2 x 1.5 V DC)	Power consumption
110 mA @ 2.4 V DC	Weight
	Batteries
750 g without batteries (batteries + 60 g)	Size

Technical data is subject to change without notice