

## HATlite-Mini



- Rubber housing for extreme rough applications
- Customized assembling of operating elements possible
- Status indication via LED for operation and battery condition
- Disposable standard AA-batteries or rechargeable batteries may be used
- Permanent operation up to 40 hours possible with rechargeable batteries of 2700 mAh
- "Listen before talk"-technology with automatic frequency management for higher operational safety or frequency hopping for USA and Canada
- Several systems can be operated at the same time without disturbing each other

Technical data is subject to change without notice

## General technical data

Temperature range	–20° to +80°C (optionally with heating foil –40° to +80°C)
Type of protection	IP 65 (higher on request)
Housing	TPE
Technology	Transceiver (bidirectional, half-duplex)
Frequency	433.075–434.775 MHz (69 channels) / Europe / 902–928Mz / USA & CANADA
Output Power	adjustable up to 10 mW
Modulation	FSK
Transmission method	TDMA (Time Division Multiple Access) for Europe; Frequency hopping for USA and Canada
Distance	approx. 300 meters / 1000 feet (depending on environment)
Supply voltage	2.0 .. 4.5 V DC (2 AA-NiMh-cells)
Power consumption	50 mA @ 2.4 V DC
Weight	397 g (without batteries), batteries + 60 g
Size	15,0 × 8,0 × 9,8 cm ( L × W × H)

Technical data is subject to change without notice